



- Available for 0.25/0.9/2/3mm fiber, no need to change clamp
- Equipped with shade cap convenient to use in strong light environment
- Compact design, self-lock trigger, free your hands
- 0.96 inch OLED screen, richer display content
- Detect frequency 270/1k/2kHz
- 700-1700nm wavelength range
- Built-in Lithium battery, Type-C port
- LED light and 10 mW VFL
- Macro bending technology
Non-destructive testing



Live Fiber Identifier Parameter

Model	FWD-01-V10
Fiber Type	0.9, 0.25, 2.0, 3.0 mm fiber
Wavelength Range	700 to 1700nm (SM)
Sensitivity	+10~-40dBm(need wavelength 1550nm)
Recognizable signal type	270Hz、1 kHz、 2kHz

Visual Fault Locator Parameter

VFL Connector	2.5mm universal connector
Frequency	2±0.5Hz
Output Power	10mW

Others

Battery	Built-in lithium battery
Battery detection	Low battery automatic shutdown
Charging Interface	5V500mA, TYPE-C
Energy Saving Mode	Yes
LED Light	Yes
Beep	Yes
Operating Temperature	-10~+50℃
Storage Temperature	-20~+70℃
Relative Humidity	<95% no condensation
Size	152mm*41mm*32mm
Weight	80g

Appearance



Front



Back



Right



Left



Bottom VFL interface